



M-M6601

6" TFT LCD monitor



ALDINET Spa
Viale C. Colombo, 8
20090 Trezzano s. Naviglio (MI)
ITALY

INSTRUCTION MANUAL

MONITOR:



1. IR
2. R/C Window
3. Power
4. Mode
5. Negative Decrease
6. Menu
7. Positive Increase

CAUTION:


For your safety, please rotate the angle of the display or turn off the display while driving.

SPECIAL STATEMENT:

LCD may have a few bright dots, which is normal for the matrix display technology, and doesn't indicate defects or faults

NOTICE:

- Please operate instruction manual completely before use;
- The unit is manufactured with precision elements pay attention to protection against dampness;
- Prevent the hard object from scratching LCD surface;
- High voltage inside non-technical authorized person is not allowed to dismantle the unit.



REMOTE CONTROL

1. Power
2. V1/V2 Change
3. Positive Increase
4. Menu
5. Negative Decrease
6. Mode Selection

Connection



MONITOR with IR

SPECIFICATIONS:

- Display size: 6 inch (16:9)
- Pixel : 1200(w)× 234(h)
- Power supply: DC 12V
- Input: Dual video input ; two stereo audio input
- System: PAL/NTSC auto switching
- All functions are controlled by remote control; OSD menu
- Mode: 16:9 and 4:3 auto switching
- Blue screen when no signal
- IR1: L channel 2.3MHZ, R channel 2.8MHZ
- IR2: L channel 3.2MHZ, R channel 3.8MHZ



深圳市永泰源电子科技有限公司

项 目	说明书	日 期	2010-8-11
品 牌	MACROM	材料要求	157克铜板纸
型 号	M-M6601	工艺要求	黑白印刷
比 例	1 : 1	文件编号	WITE/04/05-
规 格	A5	产品料号	PAC-20609900-006
备 注	ALDINET 客户	版本版次	A/0
制表	刘杰	审核	批准